

ELIA HL




Scan the QR-code for the latest information


■ Black RAL 9017 / Black RAL9017 /

LED highbay designed for indoor industrial, logistics and tertiary applications, where efficiency, high luminous output, precision and resistance are required

- Available in 3 power steps (120 W, 150 W and 200 W) with a standard colour temperature of 4,000 K (neutral white) and a colour rendering index of 80, the range allows for great flexibility with its multiple possible combinations: 3 optics options (60°, 90° and 120° beam angles in polycarbonate lenses) and 2 integrated power supply options (On/Off and DALI)
- Thanks to its black powder-coated die-cast aluminium body with incorporated heatsink, it is tough, durable (IP65 and IK08) and able to withstand harsh environmental conditions (such as ambient temperature variations from -30°C to +50°C)
- The luminaire can be suspension-mounted through the hook attachment integrated into the upper part of the device



ELIA HL
ON/OFF



ELIA HL
DALI

ELIA HL M2 120W

IP65 - IK08 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 100-240 V 50/60 Hz											
120	I	✓	80	4000	SYMM	60°	-	17900	■	GWF1000MH840	✓
120	I	✓	80	4000	SYMM	90°	-	18200	■	GWF1000ML840	✓
120	I	✓	80	4000	SYMM	120°	-	18000	■	GWF1000MM840	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
120	I	✓	80	4000	SYMM	60°	-	17900	■	GWF1001MH840	✓
120	I	✓	80	4000	SYMM	90°	-	18200	■	GWF1001ML840	✓
120	I	✓	80	4000	SYMM	120°	-	18000	■	GWF1001MM840	✓



ELIA HL M3 150W

IP65 - IK08 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 100-240 V 50/60 Hz											
150	I	✓	80	4000	SYMM	60°	-	22400	■	GWF1000NH840	✓
150	I	✓	80	4000	SYMM	90°	-	22800	■	GWF1000NL840	✓
150	I	✓	80	4000	SYMM	120°	-	22500	■	GWF1000NM840	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
150	I	✓	80	4000	SYMM	60°	-	22400	■	GWF1001NH840	✓
150	I	✓	80	4000	SYMM	90°	-	22800	■	GWF1001NL840	✓
150	I	✓	80	4000	SYMM	120°	-	22500	■	GWF1001NM840	✓



ELIA HL L2 200W

IP65 - IK08 - 750 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
Power LED 100-240 V 50/60 Hz											
200	I	✓	80	4000	SYMM	60°	-	29800	■	GWF1000QH840	✓
200	I	✓	80	4000	SYMM	90°	-	30300	■	GWF1000QL840	✓
200	I	✓	80	4000	SYMM	120°	-	30000	■	GWF1000QM840	✓
Power LED dimmable DALI - 220-240 V 50/60 Hz											
200	I	✓	80	4000	SYMM	60°	-	29800	■	GWF1001QH840	✓
200	I	✓	80	4000	SYMM	90°	-	30300	■	GWF1001QL840	✓
200	I	✓	80	4000	SYMM	120°	-	30000	■	GWF1001QM840	✓



Industrial