ELIA DL





















Scan the QR-code for the latest information

WH-RAL9016 / White RAL9016 /

Flush-mounting LED downlight for lighting entrance areas, corridors and shared

- ¬ Crafted from white power-coated die-cast aluminium with an opal diffusing shield
 ¬ Available in two power versions, with separate electronic power supply in the On/
- Off or DALI options provided as part of a kit, colour temperature of 4,000 K (neutral white) and colour rendering index of more than 80 or more than 90
- \neg It was designed to withstand temperature variations from -20°C to + 45°C, and offers protection from water and dust penetration of up to level IP54 and from shocks and impacts of up to level IK06
- \neg Light and easy to handle, ELIA DL is easy to install thanks to the connector for the electrical wiring and the quick, simple fin-locking mechanism
- ¬ External emergency kit with 3h autonomy available (to be ordered separately)





ELIA DL

ELIA DL M2 25W OPAL

IP40 - IK06 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	DIN EN 12464-1	1 CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [Im]	LUMINAIRE LUMEN OUTPUT (Im)	COLOUR / Finish	PART NUMBER	UKCA
Power L	ED 220	-240	V 50,	/60 H	Z					
25		✓	-	90	4000	_	2400		GWF1510MA940	✓
25		✓	-	80	4000	-	2600		GWF1510MA840	✓
Power L	ED dim	ımab	le DA	\LI - 2	20-240 \	/ 50/60 Hz				
25		✓	-	90	4000	-	2400		GWF1511MA940	✓
25		√	-	80	4000	_	2600		GWF1511MA840	√



ELIA DL L2 35W OPAL

IP40 - IK06 - 650 °C

CLASS	ENEC	DIN EN 12464-1	CRI	KELVIN	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER	UKCA
D 220	-240	V 50/	60 H	z					
П	✓	-	90	4000	-	3300		GWF1510QA940	✓
П	✓	-	80	4000	-	3600		GWF1510QA840	✓
D dim	mab	le DA	LI - 2	220-240 V	/ 50/60 Hz				
II	✓	-	90	4000	_	3300		GWF1511QA940	✓
- II	✓	_	80	4000	-	3600		GWF1511QA840	
	D 220 	D 220-240	D 220-240 V 50/ 	D 220-240 V 50/60 H \(- 90 \) \(- 80 \) D dimmable DALI - 2 \(- 90 \)	D 220-240 V 50/60 Hz ✓ - 90 4000 ✓ - 80 4000 D dimmable DALI - 220-240 V	D 220-240 V 50/60 Hz ✓ - 90 4000 - ✓ - 80 4000 - D dimmable DALI - 220-240 V 50/60 Hz ✓ - 90 4000 -	D 220-240 V 50/60 Hz	D 220-240 V 50/60 Hz ✓ - 90 4000 - 3300	D 220-240 V 50/60 Hz



Optional accessories

ELIA DL Emergency kit 3h	GWS2992	
DESCRIPTION	COLOR PART NUMBER	UKCA

