

GUELL 1 S/W




| | |
|--|----------------------------------|
| Part number | 3115052 |
| Lampholder: | LED |
| Light source: | LED |
| Wattage: | 51 W |
| Finishing: | GR-94 / Metallic grey / Textured |
| Insulation class: | I |
| IP degree of protection: | IP66 |
| IK-J-xxIP: | IK07 3J xx5 |
| CRI: | 80 |
| Colour temperature: | 4000 |
| Power factor / COS Φ: | 0.9 |
| Optic: | Symmetric Wide optics |
| Lightsource lumen output (lm): | 8099 lm |
| Luminaire lumen output (lm): | 6860 lm |
| L: | L90 |
| B: | B20 |
| Lifetime: | 80000 h |
| Min. ambient temperature (°C): | -20 |
| Max. ambient temperature (°C): | 35 |
| IPEA* (road lighting): | A7+ |
| IPEA* (large areas, roundabouts): | A8+ |
| IPEA* (cycle-pedestrian): | A6+ |
| IPEA* (green areas): | A6+ |
| IPEA* (historic city centers): | A11+ |
| Luminous Intensity Class: | G*6 |




Description

- LED floodlight for indoor and outdoor, comprising:
- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
 - Extra clear, toughened, flat glass diffuser
 - High-performance polished, oxidised, iridescence-free, aluminium reflector (Al 99.99)
 - Anti-ageing custom moulded silicone sealing gasket(s)
 - Cable gland M20x1.5 for cables \varnothing 10- \varnothing 14 mm
 - Stainless steel locking hardware
 - Fully integrated stainless steel aluminium spring clips
 - Powder-coated steel tiltable bracket
 - Openable and maintainable luminaire (future-proof)
 - Dimmable ballast available. Consult factory
 - Other colour temperatures (CCT) and colour rendering index (CRI) options available.
- Consult factory
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
 - Design by GIORGIO LODI

Photometric data




Technical drawings



OPTIONAL ACCESSORIES

GUELL 1



14172902
Protective grid GUELL 1



14174220
Connection box IP 66




14173394
Wall support 500 mm/19.69" GUELL
1/2

Metallic grey




14173494
Wall support 1000 mm/39.37" GUELL
1/2

Metallic grey



14453194
Single pole top support GUELL 1


Metallic grey



14453294
Double pole top support GUELL 1

Metallic grey


GUELL 1 A/W - GUELL 1 S/W



14173294
Soft glass GUELL 1

Metallic grey

GUELL 1 S/W



14173020
Louvre GUELL 1 Symmetrical

