

## GUELL 1 A/W




<b>Part number</b>	3115066
<b>Lampholder:</b>	LED
<b>Light source:</b>	LED
<b>Wattage:</b>	36 W
<b>Finishing:</b>	GR-94 / Metallic grey / Textured
<b>Insulation class:</b>	I
<b>IP degree of protection:</b>	IP66
<b>IK-J-xxIP:</b>	IK07 3J xx5
<b>CRI:</b>	70
<b>Colour temperature:</b>	5000
<b>Power factor / COS Φ:</b>	0.9
<b>Optic:</b>	Asymmetric wide reflector
<b>Lightsource lumen output (lm):</b>	6572 lm
<b>Luminaire lumen output (lm):</b>	5082 lm
<b>L:</b>	L90
<b>B:</b>	B20
<b>Lifetime:</b>	80000 h
<b>Min. ambient temperature (°C):</b>	-20
<b>Max. ambient temperature (°C):</b>	40
<b>IPEA* (road lighting):</b>	A10+
<b>IPEA* (large areas, roundabouts):</b>	A11+
<b>IPEA* (cycle-pedestrian):</b>	A9+
<b>IPEA* (green areas):</b>	A9+
<b>IPEA* (historic city centers):</b>	A15+
<b>Luminous Intensity Class:</b>	G*6




### Description

- LED floodlight for indoor and outdoor, comprising:
- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
  - Extra clear, toughened, flat glass diffuser
  - High-performance polished, oxidised, iridescence-free, aluminium reflector (Al 99.99)
  - Anti-ageing custom moulded silicone sealing gasket(s)
  - Cable gland M20x1.5 for cables Ø 10- Ø 14 mm
  - Stainless steel locking hardware
  - Fully integrated stainless steel aluminium spring clips
  - Powder-coated steel tiltable bracket
  - Openable and maintainable luminaire (future-proof)
  - Dimmable ballast available. Consult factory
  - Other colour temperatures (CCT) and colour rendering index (CRI) options available.
- Consult factory
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
  - Design by GIORGIO LODI

### Photometric data




### Technical drawings



## OPTIONAL ACCESSORIES

### GUELL 1



14172902  
Protective grid GUELL 1




14174220  
Connection box IP 66




14173394  
Wall support 500 mm/19.69" GUELL  
1/2  
  
Metallic grey



14173494  
Wall support 1000 mm/39.37" GUELL  
1/2  
  
Metallic grey




14453194  
Single pole top support GUELL 1  
  
Metallic grey




14453294  
Double pole top support GUELL 1  
  
Metallic grey

### GUELL 1 A/W - GUELL 1 S/W



14173294  
Soft glass GUELL 1  
  
Metallic grey

### GUELL 1 A/W



14173120  
Louvre GUELL 1 Asymmetrical

