

# GUELL 1




LED floodlight for indoor and outdoor lighting, comprising:

- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating
- Flat tempered glass diffuser
- Very high performance reflectors made of 99.99% plated aluminium, polished, oxidised and free of iridescence
- Anti-ageing silicone gasket


- Cable gland M20x1.5 for cables Ø 10- Ø 14 mm
- Stainless steel external screws
- Fully integrated stainless steel aluminium spring clips
- Powder coated steel bracket
- On request, versions with dimmable ballast available
- DETEK versions with a passive infrared motion detector with automatic ignition
- All versions are available with 3000K LEDs on request



● GR-94 / Metallic grey / Textured



GUELL 1



GUELL 1  
DETEK




Please visit our web site  
[www.performanceinlighting.com](http://www.performanceinlighting.com)  
for the latest updated versions available.

## GUELL 1 S/W

IK07 3J xx5

WATTAGE	CLASS	CE	CRI	KELVIN	COS Ø ≥ 0.9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
<b>Power LED 220-240 V 50/60 Hz</b>														
53 W	I	-	80	4000	✓	S/W	-	7276 lm	6092 lm	70	10	150000 h	●	<b>06105494</b>
39 W	I	-	80	4000	✓	S/W	-	5558 lm	4890 lm	70	10	150000 h	●	<b>06105794</b>

IP 66




## GUELL 1 A/W

IK07 3J xx5

WATTAGE	CLASS	CE	CRI	KELVIN	COS Ø ≥ 0.9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
<b>Power LED 220-240 V 50/60 Hz</b>														
53 W	I	-	80	4000	✓	A40/W	-	7276 lm	5950 lm	70	10	150000 h	●	<b>06106694</b>
53 W	I	-	80	3000	✓	A40/W	-	7059 lm	5773 lm	70	10	150000 h	●	<b>06106794</b>
39 W	I	-	80	4000	✓	A40/W	-	5558 lm	4712 lm	70	10	150000 h	●	<b>06106994</b>
39 W	I	-	80	3000	✓	A40/W	-	5392 lm	4588 lm	70	10	150000 h	●	<b>06107094</b>

IP 66




## GUELL 1 C/I

IK07 3J xx5

WATTAGE	CLASS	CEC	CRI	KELVIN	COS $\phi$ $\geq 0.9$	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
<b>Power LED 220-240 V 50/60 Hz</b>														
53 W	I	-	80	4000	✓	C/I	-	7276 lm	5739 lm	70	10	150000 h	●	<b>06289194</b>
39 W	I	-	80	4000	✓	C/I	-	5558 lm	4599 lm	70	10	150000 h	●	<b>06288594</b>

IP 66




## GUELL 1 C/W

IK07 3J xx5

WATTAGE	CLASS	CEC	CRI	KELVIN	COS $\phi$ $\geq 0.9$	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
<b>Power LED 220-240 V 50/60 Hz</b>														
53 W	I	-	80	4000	✓	C/W	-	8190 lm	5439 lm	70	10	150000 h	●	<b>3101115</b>
39 W	I	-	80	4000	✓	C/W	-	5992 lm	4315 lm	70	10	150000 h	●	<b>3101109</b>

IP 66




## GUELL 1 DETEK S/W

IK07 3J xx5

WATTAGE	CLASS	CEC	CRI	KELVIN	COS $\phi$ $\geq 0.9$	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
<b>Power LED 220-240 V 50/60 Hz</b>														
53 W	I	-	80	4000	✓	S/W	-	7276 lm	6092 lm	70	10	150000 h	●	<b>06119994</b>

IP 44




## GUELL 1 DETEK A/W

IK07 3J xx5

WATTAGE	CLASS	CEC	CRI	KELVIN	COS $\phi$ $\geq 0.9$	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
<b>Power LED 220-240 V 50/60 Hz</b>														
53 W	I	-	80	4000	✓	A40/W	-	7276 lm	5950 lm	70	10	150000 h	●	<b>06114894</b>
53 W	I	-	80	3000	✓	A40/W	-	7059 lm	5773 lm	70	10	150000 h	●	<b>06149394</b>

IP 44



## OPTIONAL ACCESSORIES

DESCRIPTION	COLOR	PART NUMBER
<b>GUELL 1</b>		
Protective grid GUELL 1		<b>14172902</b>
Connection box IP 66		<b>14174220</b>
Wall support 500 mm/19.69" GUELL 1/2	●	<b>14173394</b>
Wall support 1000 mm/39.37" GUELL 1/2	●	<b>14173494</b>
Single pole top support GUELL 1	●	<b>14453194</b>
Double pole top support GUELL 1	●	<b>14453294</b>
<b>GUELL 1 A/W - GUELL 1 S/W</b>		
Soft glass GUELL 1	●	<b>14173294</b>
<b>GUELL 1 A/W</b>		
Louvre GUELL 1 Asymmetrical		<b>14173120</b>
<b>GUELL 1 S/W</b>		
Louvre GUELL 1 Symmetrical		<b>14173020</b>
<b>GUELL 1 C/I</b>		
GUELL 1 C/I frosted glass	●	<b>14476594</b>

