

GUELL ZERO S/M




Part number	06149080
Lampholder:	LED
Light Source:	LED
Wattage:	15 W
Finish:	BK-RAL9005 / Black RAL9005 / Glossy
Insulation class:	I
Degree of protection:	IP66
IK-J-xxIP:	IK06 1.2J xx3
CRI:	80
Kelvin:	4000
Power factor:	$\text{COS}\phi \geq 0,9$
Optic:	Symmetric medium reflector
Lightsource lumen output:	1888 lm
Luminaire lumen output:	1484 lm
L:	L70
B:	B10
Lifetime:	150000 h
Ta MIN luminaire:	-15°
Ta MAX luminaire:	35°
ULR:	0%
IPEA* (Street Lighting):	A++
IPEA* (Area Lighting):	A3+
IPEA* (Cycle/Pedestrian Lighting):	A++
IPEA* (Green Areas):	A++
IPEA* (Historical Areas):	A5+
Luminous Intensity Class:	G*6




Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating ISO 9227
 - Flat tempered glass diffuser
 - Diffuser permanently sealed to the housing through a high temperature resistant silicone glue
 - Very high performance symmetrical reflector made of 99.99% plated aluminium, polished, oxidised and free of iridescence
 - Stainless steel external screws
 - Stainless steel locking springs for the glass
 - Powder coated steel bracket
 - Complete with 1 metre of cable H05RN-F 3G1 mm²
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings



OPTIONAL ACCESSORIES

GUELL ZERO



14453380
500 mm arm completes with
connection base GUELL ZERO

Black RAL9005



14453480
1000 mm arm completes with
connection base GUELL ZERO

Black RAL9005