

INSERT+ 3 A26/W



Part number	3100875
Lampholder:	LED
Light Source:	LED
Wattage:	26 W
Finish:	GR-94 / Metallic grey / Textured
Insulation class:	I
Degree of protection:	IP66
IK-J-xxIP:	IK10 20J xx9
CRI:	70
Kelvin:	4000
Power factor:	$\text{COS}\phi \geq 0,9$
Optic:	Asymmetric wide reflector
Lightsource lumen output:	3585 lm
Luminaire lumen output:	1399 lm
L:	L80
B:	B10
Lifetime:	125000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	35°




Description


Wall recessed luminaire, for indoor and outdoor use in solid and hollow walls, for general lighting, comprising:

- Die-cast painted aluminium housing and trim ISO 9227
- Tempered clear glass diffuser
- Diffuser in flat glass, internally frosted
- Silicone gasket
- External electrical connection with sealed plug-socket QUICK, complete with cable
- Electrical connector for wires Ø 7 - Ø 12 mm
- LED versions include 220/240 V 50/60 Hz safety transformer
- Stainless steel locking screws
- The fixture requires recessed fixing box which must be ordered separately
- Supplied with 0,5 m pre-wired H07RN-F cable
- Anti-tamper kit available as an accessory
- Available for thorough wiring as accessories. Connectors fit Ø 7 - Ø 10,5 mm and Ø 14 - Ø 17 mm cables
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings



MANDATORY ACCESSORIES

INSERT+3



3100883
Recessed box INSERT+3

Stainless steel

OPTIONAL ACCESSORIES

INSERT+ 3



3100992
Stainless steel, anti-tamper locking
screws



310495
Connection Kit Y 3-way D.14-17mm
IP68



310496
Connection Kit Y 3-way D.7-10.5mm
IP68