

## KOA LINE STR/GL S/EW



<b>Part number</b>	06247794
<b>Lampholder:</b>	LED
<b>Light Source:</b>	LED
<b>Wattage:</b>	112 W
<b>Finish:</b>	GR-94 / Metallic grey / Textured
<b>Insulation class:</b>	I
<b>Degree of protection:</b>	IP66
<b>IK-J-xxIP:</b>	IK07 2.2J xx5
<b>CRI:</b>	85
<b>Kelvin:</b>	4000
<b>Power factor:</b>	COS $\phi$ $\geq$ 0,9
<b>Optic:</b>	SYMMETRIC EXTRA WIDE REFLECTOR
<b>Lightsource lumen output:</b>	13350 lm
<b>Luminaire lumen output:</b>	9826 lm
<b>L:</b>	L80
<b>B:</b>	B10
<b>Lifetime:</b>	60000 h
<b>Ta MIN luminaire:</b>	-15°
<b>Ta MAX luminaire:</b>	35°




### Description


Range of indoor and outdoor LED fixtures, comprising:

- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating
- Diffusor made of extra clear, flat glass, tempered, markings with serigraphy, internally ice etched
- Anti-aging silicone gasket with high resiliency
- Electrical connection with outdoor rated plug & socket quick connector (IP66) that allows connection to mains without opening the luminaire. Made in PA66 with silver-plated brass contacts, for cables  $\varnothing$  9 -  $\varnothing$  12 mm
- Light beam obtained by the combination of multiple LED modules
- Galvanised steel suspension hooks
- Stainless steel external screws
- In order to allow the use of these devices in various installation situations - on the wall, the ceiling, or a post - a wide range of accessories is available.
- In order to guarantee resistance to wind forces, we suggest using the installation systems available as accessories for outdoor spaces.
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

### Photometric data



### Technical drawings




## OPTIONAL ACCESSORIES

### KOA LINE



14471694  
KOA LINE mounting bracket



14471894  
Pair of AISI 304 stainless steel  
mounting brackets KOA LINE




14471494  
Single pole top Ø 60-76 mm support  
KOA LINE



14471594  
Double pole top Ø 60-76 mm KOA  
LINE support



14471794  
Pair of mounting brackets with  
stainless steel clamps for Ø33-42mm  
pole / rail installation



14006902  
Galvanized steel protection grid, for  
ceiling mounting