

LAMA+ MINI S/W



Part number	3101187
Lampholder:	LED
Light Source:	LED
Wattage:	39 W
Finish:	WH-87 / White / Textured
Insulation class:	I
Degree of protection:	IP66
IK-J-xxIP:	IK06 1J xx3
CRI:	80
Kelvin:	4000
Power factor:	$\cos\phi \geq 0,9$
Optic:	SYMMETRIC WIDE REFLECTOR
Lightsource lumen output:	6048 lm
Luminaire lumen output:	4725 lm
L:	L70
B:	B10
Lifetime:	60000 h
Ta MIN luminaire:	-25°
Ta MAX luminaire:	45°




Description

Suspended LED fixture series for indoors, made up of:

- Housing and cap in die-cast aluminium with polyester powder coating after surface chemical conversion treatment
- Flat extra clear tempered glass diffuser
- High-transparency polycarbonate lenses for best light transmission
- Anti-aging silicone gasket with high resiliency
- Electrical connection with outdoor rated plug & socket quick connector (IP66) that allows connection to mains without opening the luminaire. Made in PA66 with silver-plated brass contacts, for cables Ø 9 - Ø 12 mm
- Galvanised steel suspension hooks
- Stainless steel external screws
- Stainless steel locking springs for the glass
- EM versions are complete with emergency device that can operate on battery for 1 hour. Product can be used for general or emergency lighting.
- Versions are available with ON-OFF driver and dimmable DALI
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings

