

LAMA+ MINI S/W




Part number	3101194
Lampholder:	LED
Light Source:	LED
Wattage:	52 W
Finish:	WH-87 / White / Textured
Insulation class:	I
Degree of protection:	IP66
IK-J-xxIP:	IK06 1J xx3
CRI:	80
Kelvin:	4000
Power factor:	COS ϕ $\geq$ 0,9
Optic:	SYMMETRIC WIDE REFLECTOR
Lightsources lumen output:	8064 lm
Luminaire lumen output:	6117 lm
L:	L70
B:	B10
Lifetime:	60000 h
Ta MIN luminaire:	-25°
Ta MAX luminaire:	35°



Description

- Suspended LED fixture series for indoors, made up of:
- Housing and cap in die-cast aluminium with polyester powder coating after surface chemical conversion treatment
 - Flat extra clear tempered glass diffuser
 - High-transparency polycarbonate lenses for best light transmission
 - Symmetrical lens
 - Anti-aging silicone gasket with high resiliency
 - Electrical connection with outdoor rated plug & socket quick connector (IP66) that allows connection to mains without opening the luminaire. Made in PA66 with silver-plated brass contacts, for cables Ø 9 - Ø 12 mm
 - Galvanised steel suspension hooks
 - Stainless steel external screws
 - Stainless steel locking springs for the glass
 - Dimmable DALI
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings

