

LAMA+ MINI S/EW




| | |
|----------------------------------|--------------------------------|
| Part number | 3101199 |
| Lampholder: | LED |
| Light Source: | LED |
| Wattage: | 39 W |
| Finish: | WH-87 / White / Textured |
| Insulation class: | I |
| Degree of protection: | IP66 |
| IK-J-xxIP: | IK06 1J xx3 |
| CRI: | 80 |
| Kelvin: | 4000 |
| Power factor: | COS ϕ \geq 0,9 |
| Optic: | SYMMETRIC EXTRA WIDE REFLECTOR |
| Lightsource lumen output: | 6048 lm |
| Luminaire lumen output: | 4988 lm |
| L: | L70 |
| B: | B10 |
| Lifetime: | 60000 h |
| Ta MIN luminaire: | -25° |
| Ta MAX luminaire: | 45° |



Description

- Suspended LED fixture series for indoors, made up of:
- Housing and cap in die-cast aluminium with polyester powder coating after surface chemical conversion treatment
 - Flat extra clear tempered glass diffuser
 - High-transparency polycarbonate lenses for best light transmission
 - Anti-aging silicone gasket with high resiliency
 - Electrical connection with outdoor rated plug & socket quick connector (IP66) that allows connection to mains without opening the luminaire. Made in PA66 with silver-plated brass contacts, for cables \varnothing 9 - \varnothing 12 mm
 - Galvanised steel suspension hooks
 - Stainless steel external screws
 - Stainless steel locking springs for the glass
 - EM versions are complete with emergency device that can operate on battery for 1 hour.
- Product can be used for general or emergency lighting.
- Versions are available with ON-OFF driver and dimmable DALI
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings

