

LM4 S/EW



Part number	3101708
Lampholder:	LED
Light Source:	LED
Wattage:	101 W
Finish:	GR-94 / Metallic grey / Textured
Insulation class:	I
Degree of protection:	IP66
IK-J-xxIP:	IK06 0.80J xx3
CRI:	80
Kelvin:	4000
Power factor:	$\text{COS}\phi \geq 0,9$
Optic:	SYMMETRIC EXTRA WIDE REFLECTOR
Lightsource lumen output:	16272 lm
Luminaire lumen output:	12213 lm
L:	L70
B:	B10
Lifetime:	60000 h
Ta MIN luminaire:	-40°
Ta MAX luminaire:	30°




Description

Range of indoor and outdoor LED fixtures, comprising:

- Housing and cap in die-cast aluminium with polyester powder coating after surface chemical conversion treatment
 - Diffusor made of extra clear, flat glass, tempered, markings with serigraphy, internally ice etched
 - Anti-aging silicone gasket with high resiliency
 - Electrical connection with outdoor rated plug & socket quick connector (IP66) that allows connection to mains without opening the luminaire. Made in PA66 with silver-plated brass contacts, for cables Ø 9 - Ø 12 mm
 - Stainless steel external screws
 - Stainless steel locking springs for the glass
 - Stainless steel springs for quick ceiling mount
 - 3000 K and 5000 K available upon request
 - EM versions are complete with emergency device that can operate on battery for 1 hour.
- Product can be used for general or emergency lighting.
- Versions are available with ON-OFF driver and dimmable DALI
 - Through-wiring version available upon request
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings

