




# GUELL 2.5+ A/W

Part number LTF1622FA83o



## Description

LED floodlight for indoor and outdoor, comprising:

- Die-cast aluminium housing, polyester powder coat finish ISO 9227/12944 - ISO 9223 (C5)
- Extra clear, toughened, flat glass diffuser
- High-performance polished, oxidised, iridescence-free, aluminium reflector (Al 99.99)
- Anti-ageing custom moulded silicone sealing gasket(s)
- M20x1.5 cable gland for cables Ø10-Ø14 mm
- Stainless steel locking hardware
- Fully integrated stainless steel aluminium spring clips
- Powder-coated steel tiltable bracket
- Openable and maintainable luminaire (future-proof)
- Protected against power surges up to 10 kV
- Other colour temperatures (CCT) and colour rendering index (CRI) options available. Consult factory
- Design by GIORGIO LODI

To maintain the regular updating of our products, PERFORMANCE in LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website [www.performanceinlighting.com](http://www.performanceinlighting.com). Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at <https://www.performanceinlighting.com/qr/company/led-warranty>

## Product data

|             |          |             |          |
|-------------|----------|-------------|----------|
| ETIM Group: | EG000027 | ETIM Class: | EC001744 |
|-------------|----------|-------------|----------|

## General information

|                                    |                                  |                              |       |
|------------------------------------|----------------------------------|------------------------------|-------|
| Lampholder:                        | LED                              | Light source:                | LED   |
| Lightsource lumen output [lm]:     | 24906                            | Luminaire lumen output [lm]: | 20315 |
| Luminaire wattage [W]:             | 153 W                            | Luminous efficacy [lm/W]:    | 133   |
| CRI:                               | 80                               | Colour temperature [K]:      | 3000  |
| Colour / Finishing:                | GR-94 / Metallic grey / Textured | IP degree of protection:     | IP66  |
| Impact resistance / impact energy: | IK07 3J xx5                      | Protection class:            | I     |
| Optic:                             | A40/W - Asymmetric Wide          | Net weight [kg]:             | 6.184 |
| Overall length [mm]:               | 355                              | Overall width [mm]:          | 425   |
| Overall height [mm]:               | 85                               |                              |       |

## Mechanical features

|                            |             |                            |           |
|----------------------------|-------------|----------------------------|-----------|
| Shape:                     | Rectangular | Housing material:          | Aluminium |
| Diffuser material:         | Glass       | Glow wire test [°C]:       | 650 Å°C   |
| Frontal exposed area [m²]: | 0.03        | Lateral exposed area [m²]: | 0.03      |
| Top exposed area [m²]:     | 0.14        |                            |           |

## Electrical features

|                                 |           |                                       |          |
|---------------------------------|-----------|---------------------------------------|----------|
| Voltage type:                   | AC        | Input voltage [V AC]:                 | 100/305  |
| Input frequency [Hz]:           | 50/60     | Power factor / COS Φ:                 | >0.9     |
| Surge protection   Common [kV]: | 10.000000 | Surge protection   Differential [kV]: | 6.000000 |
| Inrush current [A/μs]:          | 110 / 200 | C10 1.5 mm²:                          | 6        |
| C16 2.5 mm²:                    | 10        | B10 1.5 mm²:                          | 3        |
| B16 2.5 mm²:                    | 6         |                                       |          |

## Installation

|                                        |         |                                |                         |
|----------------------------------------|---------|--------------------------------|-------------------------|
| Application area:                      | Outdoor | Mounting type:                 | Professional floodlight |
| Min. ambient temperature [°C]:         | -40     | Max. ambient temperature [°C]: | 40                      |
| Min. distance from lighted object [m]: | 1.00    |                                |                         |

## Light features

|                                  |        |                                   |               |
|----------------------------------|--------|-----------------------------------|---------------|
| MacAdam:                         | 3      | Lumen maintenance:                | L80B10@78000h |
| Distribution of light emission:  | Direct | DFF - Downward Flux Fraction [%]: | 100           |
| UFF - Upward Flux Fraction [%]:  | 0      | Luminous Intensity Class:         | G*6           |
| Zero light pollution (ULR = 0%): |        | IPEA* (road lighting):            | A3+           |


To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website [www.performanceinlighting.com](http://www.performanceinlighting.com). Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at <https://www.performanceinlighting.com/qr/company/led-warranty>

|                                   |     |
|-----------------------------------|-----|
| IPEA* (large areas, roundabouts): | A7+ |
| IPEA* (green areas):              | A4+ |

|                                |     |
|--------------------------------|-----|
| IPEA* (cycle-pedestrian):      | A4+ |
| IPEA* (historic city centers): | A9+ |


To maintain the regular updating of our products, PERFORMANCE in LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website [www.performanceinlighting.com](http://www.performanceinlighting.com). Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at <https://www.performanceinlighting.com/qr/company/led-warranty>

## Photometric data



## Optional accessories

### GUELL 2.5+



#### LTF1A3652

Louvre GUELL 2.5+


■ GR-94 / Metallic grey



#### LTF1A5603

Protective grid GUELL 2.5+


□ GS1



#### 14012294

Steel 'U' bolt clamp for Ø 60-80 mm poles painted aluminium grey


■ GR-94 / Metallic grey



#### 310966

Single pole top support GUELL 2.5

■ GR-94 / Metallic grey



#### 310967

Double pole top support GUELL 2.5

■ GR-94 / Metallic grey

To maintain the regular updating of our products, PERFORMANCE iN LIGHTING reserves the right to make changes without prior notice. For the most up to date information we always recommend you read the latest version published on the website [www.performanceinlighting.com](http://www.performanceinlighting.com). Delivered luminaire lumen outputs and power consumptions, including losses, are subject to a tolerance of +/- 7%, and unless otherwise stated the values apply to an ambient temperature of 25°C. Terms of warranty are available at <https://www.performanceinlighting.com/gr/company/led-warranty>