


MASK+ MINI B



Part number	3102529
Lampholder:	LED
Light Source:	LED
Wattage:	16 W
Finish:	AN-96 / Anthracite gray / Textured
Insulation class:	I
Degree of protection:	IP65
IK-J-xxIP:	IK05 0.70J xx3
CRI:	80
Kelvin:	4000
Power factor:	$\cos\phi \geq 0,9$
Optic:	Symmetric extra wide reflector
Lightsource lumen output:	1450 lm
Luminaire lumen output:	670 lm
L:	L70
B:	B10
Lifetime:	54000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	35°




Description

Indoor and outdoor wall-mount fixture, including:

- ISO 9227 painted die-cast aluminium housing
- Glass diffuser, internally painted for homogeneous diffused light
- Mains voltage 220-240V 50/60Hz LED module protected against surges up to 500 V
- Silicone gasket
- M versions, i.e. single emission, are supplied with a single light source and are designed to allow a single sided light output either upwards or downwards
- Double-emission (B) versions are equipped with two separate switches in order to provide upward and downward emission (DA)
- DETEK versions available on request
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings

