


NORMA+ 60 CL



Part number	305941
Lampholder:	LED
Light Source:	LED
Wattage:	27 W
Finish:	GR-RAL7035 / Grey RAL7035 / Matt
Insulation class:	I
Degree of protection:	IP65
IK-J-xxIP:	IK09 15J xx7
CRI:	80
Kelvin:	4000
Power factor:	$\text{COS}\phi \geq 0,9$
Optic:	Symmetric extra wide reflector
Lightsource lumen output:	4077 lm
Luminaire lumen output:	3258 lm
L:	L80
B:	B10
Lifetime:	44000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	45°




Description

Weatherproof LED luminaire, comprising:

- UV stabilised co-extruded polycarbonate body with double finish; satin-finish for the optical compartment and matte finish for the auxiliary electrical compartment.
- Technopolymers end caps
- Anti-ageing silicone gasket
- Tool-less bayonet opening polycarbonate cap for power connection
- The CL (Continuous Line) versions are suitable for through wiring continuous line installations (5x2,5 mm²)
- Cable gland M20x1.5 for cables Ø 10- Ø 14 mm
- Luminaire complete with through wiring for power supply to a continuous row
- Aluminium heat sink
- Stainless steel springs for quick installation
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings

