


QUASAR 60 DOUBLE TECH



Part number	3100849
Lampholder:	LED
Light Source:	LED
Wattage:	38 W
Finish:	AN-96 / Anthracite gray / Textured
Insulation class:	I
Degree of protection:	IP65
IK-J-xxIP:	IK07 2J xx5
CRI:	80
Kelvin:	3000
Power factor:	$\cos\phi \geq 0,9$
Optic:	Asymmetric extra wide reflector
Lightsource lumen output:	5107 lm
Luminaire lumen output:	4026 lm
L:	L80
B:	B10
Lifetime:	130000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	35°




Description

Range of indoor and outdoor wall mounted LED fixtures, comprising:

- Die-cast painted aluminium housing ISO 9227
- Glass diffuser, internally painted for homogeneous diffused light
- Flat microprismatic glass diffuser internally pattern for TECH versions
- Reflector in satin finish pure aluminium (Al 99.98)
- Silicone gasket
- EM/3P version is designed for multipurpose and 3 hours sustained emergency lighting
- EM/3P versions are meant to be wired on a branch from the LED board working as both general and emergency lighting.
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings

