


QUASAR 10

design by R. FIORATO - F. PAGLIARINI



- GR-94 / Metallic grey / Textured
- AN-96 / Anthracite gray / Textured
- WH-87 / White / Textured




YouTube video





Range of indoor and outdoor wall mounted LED fixtures, comprising:



- Die-cast painted aluminium housing
- Secured diffuser in printed transparent flat glass
- Polymer gasket
- Stainless steel fastening screws and dowels
- Built-in driver





QUASAR 10
1WB




QUASAR 10
2WB



QUASAR 10
4WB




QUASAR 10
1NB+1WB



Package size

37 x 15 x 25 cm
(master x 6)


Fixing holes



QUASAR 10 1WB

IK02 0,20J xx0


LAMPHOLDER	WATTAGE	CLASS		CRI	KELVIN	COS Ø ≥ 0,9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
Power LED 220-240 V 50/60 Hz															
LED	3,5 W	I		80	4000	•	R	-	230 lm	122 lm	80	10	50000 h	●	303355
LED	3,5 W	I		80	3000	•	R	-	150 lm	100 lm	80	10	50000 h	●	303354
LED	3,5 W	I		80	4000	•	R	-	230 lm	122 lm	80	10	50000 h	●	303357
LED	3,5 W	I		80	3000	•	R	-	150 lm	100 lm	80	10	50000 h	●	303356
LED	3,5 W	I		80	4000	•	R	-	230 lm	122 lm	80	10	50000 h	○	303451
LED	3,5 W	I		80	3000	•	R	-	150 lm	100 lm	80	10	50000 h	○	303450



QUASAR 10 2WB

IK02 0,20J xx0


LAMPHOLDER	WATTAGE	CLASS		CRI	KELVIN	COS Ø ≥ 0,9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
Power LED 220-240 V 50/60 Hz															
LED	6 W	I		80	4000	•	R	-	460 lm	235 lm	80	10	50000 h	●	303361
LED	6 W	I		80	3000	•	R	-	300 lm	192 lm	80	10	50000 h	●	303360
LED	6 W	I		80	4000	•	R	-	460 lm	235 lm	80	10	50000 h	●	303363
LED	6 W	I		80	3000	•	R	-	300 lm	192 lm	80	10	50000 h	●	303362
LED	6 W	I		80	4000	•	R	-	460 lm	235 lm	80	10	50000 h	○	303453
LED	6 W	I		80	3000	•	R	-	300 lm	192 lm	80	10	50000 h	○	303452



QUASAR 10 4WB

IK02 0,20J xx0

LAMPHOLDER	WATTAGE	CLASS		CRI	KELVIN	COS Ø ≥ 0,9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
Power LED 220-240 V 50/60 Hz															
LED	10,8 W	I		80	4000	•	R	-	920 lm	402 lm	80	10	50000 h	●	303349
LED	10,8 W	I		80	3000	•	R	-	600 lm	329 lm	80	10	50000 h	●	303348
LED	10,8 W	I		80	4000	•	R	-	920 lm	402 lm	80	10	50000 h	●	303351
LED	10,8 W	I		80	3000	•	R	-	600 lm	329 lm	80	10	50000 h	●	303350
LED	10,8 W	I		80	4000	•	R	-	920 lm	402 lm	80	10	50000 h	○	303449
LED	10,8 W	I		80	3000	•	R	-	600 lm	329 lm	80	10	50000 h	○	303448



QUASAR 10 1NB+1WB

IK02 0,20J xx0

LAMPHOLDER	WATTAGE	CLASS		CRI	KELVIN	COS Ø ≥ 0,9	OPTIC	OPTIC BEAM	LIGHTSOURCE LUMEN OUTPUT	LUMINAIRE LUMEN OUTPUT	L	B	LIFETIME	COLOUR/ RAL	PART NUMBER
Power LED 220-240 V 50/60 Hz															
LED	6 W	I		80	4000	•	R	-	460 lm	141 lm	80	10	50000 h	●	303367
LED	6 W	I		80	3000	•	R	-	300 lm	113 lm	80	10	50000 h	●	303366
LED	6 W	I		80	4000	•	R	-	460 lm	141 lm	80	10	50000 h	●	303369
LED	6 W	I		80	3000	•	R	-	300 lm	113 lm	80	10	50000 h	●	303368
LED	6 W	I		80	4000	•	R	-	460 lm	141 lm	80	10	50000 h	○	303455
LED	6 W	I		80	3000	•	R	-	300 lm	113 lm	80	10	50000 h	○	303454

