

SL629 PL CM PRISM D/I




Part number	8629461543418
Lampholder:	LED
Light Source:	LED
Wattage:	54 W
Finish:	WH-RAL9016 / White RAL9016 / Textured
Insulation class:	I
Degree of protection:	IP20
IK-J-xxIP:	IK05 0.70J xx3
CRI:	80
Kelvin:	4000
Power factor:	COS ϕ \geq 0,9
EEL:	A2
Optic:	Symmetric uniform direct-indirect light
Optic Beam:	2 x 41°/52°
Lightsource lumen output:	8900 lm
Luminaire lumen output:	6230 lm
L:	L80
B:	B10
Lifetime:	50000 h
Ta MIN luminaire:	10°
Ta MAX luminaire:	40°




Description

- Suspended luminaire systems, consisting of one or more luminaire modules and individually selectable components.
- Housing made of steel sheet
 - Connecting elements and end pieces made of die-cast aluminium, powder-coated
 - Prismatic cover for efficient light diffusion, glare reduction and a high level of uniformity.
 - Light distribution direct or direct/ indirect
 - Colour rendering index Ra > 80
 - Colour tolerance according to MacAdam \leq 3 SDCM
 - VDU application suitable acc. to EN 12464-1
 - Special colour versions available upon request
 - Please have a look for the components at the list of accessories

Photometric data



Technical drawings



OPTIONAL ACCESSORIES

SL629PL CM



862932210
SL629 Starter kit/ending kit RAL9016
White RAL9016



862932310
SL629 Connection kit RAL9016
White RAL9016