


SL787+ PL OP



Part number	3109606
Lampholder:	LED
Wattage:	10 W
Finish:	GR-EV1 / Anodised grey / Matt
Insulation class:	I
Degree of protection:	IP30
IK-J-xxIP:	IK05 0.70J xx3
CRI:	80
Kelvin:	4000
Power factor:	$\cos\phi \geq 0,9$
EEL:	A2
Optic:	Symmetric direct lighting
Optic Beam:	$2 \times 48^\circ/51^\circ$
Lightsource lumen output:	1720 lm
Luminaire lumen output:	1530 lm
L:	L80
B:	B10
Lifetime:	50000 h
Ta MIN luminaire:	10°
Ta MAX luminaire:	40°




Description

Suspended, LED luminaire for indoor, comprising:

- Extruded anodised aluminium housing
- Die-cast aluminium end caps, painted
- Opal PMMA diffuser for optimal light diffusion and uniformity
- Streamlined, simple design with flush end caps
- High-quality workmanship of profile connections for a perfect look
- High economic efficiency thanks to luminaire efficiencies of up to 159 lm/W
- UGR <19 for all luminosities
- Through-wiring designed
- Simple and convenient lighting installation
- Interchangeable lighting inserts
- Direct light distribution
- Colour rendering index $R_a > 80$
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Complete with steel suspension cable (1.5 m), transparent power cable and canopy
- Many other luminaire designs and strip light configurations are available at www.light-performer.com

Photometric data



Technical drawings

