

SPIDER+ 30 S/W




Part number	3106055
Lampholder:	LED
Light Source:	LED
Wattage:	74/101 W
Finish:	BK-81 / Black / Textured
Insulation class:	I
Degree of protection:	IP67
IK-J-xxIP:	IK06 1.2J xx3
CRI:	80
Kelvin:	3000
Power factor:	COS ϕ \geq 0,9
Optic:	Symmetric wide reflector
Lightsource lumen output:	13354 lm
Luminaire lumen output:	11486 lm
L:	L70
B:	B10
Lifetime:	70000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	30°
ULR:	0%
IPEA* (Street Lighting):	A++
IPEA* (Area Lighting):	A5+
IPEA* (Cycle/Pedestrian Lighting):	A++
IPEA* (Green Areas):	A++
IPEA* (Historical Areas):	A6+
Luminous Intensity Class:	G*6




Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Die-cast aluminium housing chemically pre-treated and painted with polyester powder coating
 - Extra-clear flat tempered glass diffuser internally screen-printed
 - Diffuser permanently sealed to the housing through a high temperature resistant silicone glue
 - Extra pure polished aluminium reflectors
 - Symmetrical lens
 - Anti-ageing silicone gasket
 - Electrical connection through an IP68 quick external socket-plug connector that makes it possible to connect it to the network without opening the lighting element, made of techno-polymer, 3 poles x 1.5/2.5 mm², for wires ϕ 8 - ϕ 12 mm
 - Luminaire designed to operate with two predetermined power levels that can be selected by the user with the external button
 - Stainless steel external screws
 - Cataphoretic process polyester powder-coated steel bracket with simplified mounting system
 - Complete with magnetic level to be placed on the bracket at the time of mounting
 - The luminous flux data shown refers to the maximum power
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings





14174220
Connection box IP 66