

SPIDER+ 10 KIT S/EW




Part number	3108612
Lampholder:	LED
Light Source:	LED
Wattage:	10 W
Finish:	BK-81 / Black / Textured
Insulation class:	I
Degree of protection:	IP66
IK-J-xxIP:	IK06 1J xx3
CRI:	80
Kelvin:	3000
Power factor:	COS ϕ \geq 0,9
Optic:	Symmetric extra wide reflector
Lightsource lumen output:	1350 lm
Luminaire lumen output:	611 lm
L:	L70
B:	B10
Lifetime:	35000 h
Ta MIN luminaire:	-20°
Ta MAX luminaire:	25°
ULR:	0%
IPEA* (Historical Areas):	B
Luminous Intensity Class:	G*6




Description

- LED floodlight for indoor and outdoor lighting, comprising:
- Painted, die-cast aluminium housing, in compact size
 - Extra-clear, tempered, flat glass diffuser, screen-printed inside
 - Waterproof cable gland M16x1.5 for cables \varnothing 5- \varnothing 10 mm
 - Driver On Board 220-240V 50/60Hz LED module protected against surges up to 500 V
 - Stainless steel external screws
 - Painted steel bracket
 - SPIDER+ 10 KIT models are equipped with a technopolymer ground spike and 3 metres cable H05RN-F 3G1 mm²
 - Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings



OPTIONAL ACCESSORIES

SPIDER+ 10 - SPIDER+ 10 KIT



310496
Connection Kit Y 3-way D.7-10.5mm
IP68



310495
Connection Kit Y 3-way D.14-17mm
IP68