

TYK+ 10 C/M



Part number	3107286
Lampholder:	LED
Light Source:	LED
Wattage:	7 W
Finish:	AN-96 / Anthracite gray / Textured
Insulation class:	I
Degree of protection:	IP66
IK-J-xxIP:	IK06 1.2J xx3
CRI:	80
Kelvin:	4000
Power factor:	$\text{COS}\phi \geq 0,9$
Optic:	Medium circle reflector
Optic Beam:	34°
Lightsource lumen output:	700 lm
Luminaire lumen output:	598 lm
L:	L90
B:	B10
Lifetime:	75000 h
Glass temperature:	55°
Ta MIN luminaire:	-20°
Ta MAX luminaire:	40°
ULR:	0%




Description


LED floodlight for indoor and outdoor lighting, comprising:

- Die-cast aluminium housing, powder-polyester coated ISO 9227
- Extra-clear, tempered, flat glass diffuser, screen-printed inside
- Diffuser permanently sealed to the housing through a high-temperature resistant silicone
- High-transparency polycarbonate lenses grant an optimized light transmission
- Circular optic
- High resiliency anti-ageing silicone gasket with high elastic return capacity
- Tear-proof nickelled brass cable gland M16x1.5 for cables Ø 5 mm- Ø 10 mm
- Stainless steel external screws
- Stainless steel wall-mounting bracket
- Complete with 1 metre of cable H05RN-F 3G1 mm²
- Graduated goniometer for aiming purposes made in stainless steel
- Photometric data measure according to UNI EN 13032-4 and IES LM-79-08

Photometric data



Technical drawings



OPTIONAL ACCESSORIES

TYK+ 10



700191
Ground spike

Black



3108556
Extra rotation bracket +25°/-90°

Stainless steel