

WL270 OPAL




| | |
|----------------------------------|----------------------------------|
| Part number | 3105559 |
| Lampholder: | LED |
| Light Source: | LED |
| Wattage: | 24 W |
| Finish: | GR-94 / Metallic grey / Textured |
| Insulation class: | II |
| Degree of protection: | IP20 |
| IK-J-xxIP: | IK05 0.70J xx3 |
| CRI: | 80 |
| Kelvin: | 4000 |
| Power factor: | COS ϕ \geq 0,9 |
| EEL: | A1 |
| Optic: | Symmetric direct lighting |
| Lightsource lumen output: | 3300 lm |
| Luminaire lumen output: | 2650 lm |
| L: | L80 |
| B: | B10 |
| Lifetime: | 50000 h |
| Ta MIN luminaire: | 10° |
| Ta MAX luminaire: | 40° |



Description

- Wall and ceiling mounted LED luminaire for indoors, comprising:
- Die-cast aluminium housing, powder-coated
 - Light orienting technopolymer optic for a homogenous light distribution over the entire area of the cover
 - Direct light distribution
 - Light colour can be selected between 3000K and 4000K
 - Two power levels can be set via a switch
 - Colour rendering index Ra > 80
 - Colour tolerance according to MacAdam \leq 3 SDCM
 - Complete with electric converter
 - Through wiring

Photometric data



Technical drawings

