


WL ROUND




Scan the QR-code for the latest information

■ GR-94 / Metallic grey / Textured


Wall and ceiling mounted LED luminaire for indoor, comprising:

- Technopolymer housing (WL220/WL270)
- Die-cast aluminium housing, powder-coated (WL400)
- Light orienting technopolymer optic for a homogenous optimised distribution over the entire area of the diffuser
- Direct light distribution
- Light colour can be selected between 3000K and 4000K, field adjustable
- Two power levels can be set via a switch
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Built-in driver
- Through wiring




max 0,9 kg

WL
220 OPAL



max 1,5 kg

WL
270 OPAL



max 2,8 kg

WL
400 OPAL

WL220 OPAL

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER
Power LED 220-240 V 50/60 Hz										
15	II	-	80	4000	S/A	-	1900	1550	■	3105557



WL270 OPAL

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER
Power LED 220-240 V 50/60 Hz										
24	II	-	80	4000	S/A	-	3300	2650	■	3105559
Power LED - dimmable DALI 220-240 V 50/60 Hz										
24	II	-	80	3000/4000	S/B	-	3300	2650	■	3118565
Power LED 220-240 V 50/60 Hz + HF Sensor										
24	II	-	80	3000/4000	S/B	-	3300	2650	■	3118562



WL400 OPAL

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE (W)	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT (lm)	LUMINAIRE LUMEN OUTPUT (lm)	COLOUR / FINISH	PART NUMBER
Power LED 220-240 V 50/60 Hz										
38	II	-	80	4000	S/A	-	4800	3890	■	3105561
Power LED - dimmable DALI 220-240 V 50/60 Hz										
38	II	-	80	3000/4000	S/B	-	4800	3890	■	3118564



WL SQUARE




Scan the QR-code for the latest information

■ GR-94 / Metallic grey / Textured


Wall and ceiling mounted LED luminaire for indoor, comprising:

- Technopolymer housing (WL210/WL260)
- Die-cast aluminium housing, powder-coated (WL390)
- Light orienting technopolymer optic for a homogenous optimised distribution over the entire area of the diffuser
- Direct light distribution
- Light colour can be selected between 3000K and 4000K, field adjustable
- Two power levels can be set via a switch
- Colour tolerance according to MacAdam ≤ 3 SDCM
- Through wiring
- Built-in driver





max 0,9 kg

WL
210 OPAL



max 1,6 kg

WL
260 OPAL



max 2,8 kg

WL
390 OPAL

WL210 OPAL

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER
Power LED 220-240 V 50/60 Hz										
15	II	-	80	4000	S/A	-	2000	1620	■	3105556



WL260 OPAL

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER
Power LED 220-240 V 50/60 Hz										
24	II	-	80	4000	S/A	-	3350	2720	■	3105558



WL390 OPAL

IP20 - IK05 - 650 °C

LUMINAIRE WATTAGE [W]	CLASS	ENEC	CRI	KELVIN	OPTIC	BEAM ANGLE	LIGHTSOURCE LUMEN OUTPUT [lm]	LUMINAIRE LUMEN OUTPUT [lm]	COLOUR / FINISH	PART NUMBER
Power LED 220-240 V 50/60 Hz										
38	II	-	80	4000	S/A	-	5000	4020	■	3105560

