

**Surface-mounted luminaire** - Parabolic louvre, silky matt - direct distribution

Sheet steel housing, rectangular cross-section, plastic end faces with integrated light run connectors; Housing colour traffic white RAL 9016; Direct light distribution using reflectivity-enhanced parabolic aluminium louvre, silk matt anodised, for workstations, 65°<1000 cd/m<sup>2</sup> omnidirectional glare suppression according to the current DIN EN 12464-1 standard, self-engaging, can be folded down on both sides; louvre is optically seamless for light run mounting. Neutral white light colour (840) with very good colour consistency and high colour rendering Ra=80; Electrical connection via 3-pole connection terminal with plug-in contacts. Can be mounted on mounting rail. Necessary accessories available on request.

**CHARACTERISTICS**

Order number	65040024160
EAN-number	4020863281060
Commodity code	94051098
Certification mark	IP 20, Protection class I, VDU 65°<1000, ENEC10 VDE, F, Indoor, CE
Impact resistance (IK rating)	IK03
Ambient temperatur	ta 25°C

**ELECTRICAL ENGINEERING**

Operating device	Electronic driver (1 pcs.)
System output	26 W
Mains voltage	230 V / 50 Hz
Energy efficiency class	A++

**LIGHTING TECHNOLOGY**


Configuration	LED, Colour rendering/Light colour CRI ≥ 80 / 4000K
Luminaire luminous flux	3875 lm
LED service life	50000h L80/B10 (Tq 25°C)
Luminaire luminous efficacy	147 lm/W
UGR 4H/8H	UGR ≤ 19

**MECHANICS**

Colour of the housing	traffic white RAL 9016
Dimensions LxWxH/DxH	1488 x 140 x 69 mm
Weight (net)	4.64 kg
Cable entry KE X/Y	225 mm / -41 mm
Mounting method	Surface single mounting, Surface light run mounting, Mounting rail mounting

**DEEP-LINK**

<https://www.regiolux.de/en/article/65040024160>



Configuration	LED 3900 840
ηLB	100 %
Φ ↓/↑	100 % / 0 %
UGR lat./long.	15.3 / 18.9
VDU	65° < 1000cd/m <sup>2</sup>

