

universal-mounting rail - Universal mounting rail, economical, current taps every 2302.5 mm, for device mount module /2250

Torsion-resistant support rail made of galvanised, profiled sheet steel with zinc coating combined with polyester resin paint guarantees good corrosion protection; universal support rail can be used for light runs of all protection types IP20 to IP64; Housing colour traffic white RAL 9016; Heat-resistant, through-wiring with individual conductors installed in the factory. Including current tap for electrical connection of the device mounts, in module 2250. With push connection at the end of the mounting rail for the fast electrical connection of further mounting rails. 2 pre-scored knock-outs at the top allow a direct feed via the mounting rail. Can be optionally equipped with device mounts. Feed adapter and optional mounting rail including outfeed required. Please order assembly accessories as well as rail end pieces and connectors separately.

CHARACTERISTICS

| | |
|--------------------|--|
| Order number | 19282251100 |
| EAN number | 4020863423330 |
| Commodity code | 94059900 |
| Certification mark | IP 20/40/54/64, Protection class I, Indoor, CE |

ELECTRICAL ENGINEERING

| | |
|--------|----------------------|
| Wiring | 7x2.5mm ² |
|--------|----------------------|

MECHANICS

| | |
|------------------------|--|
| Housing colour | traffic white RAL 9016 |
| Dimensions (LxWxH/DxH) | 2302.5mm x 63mm x 46mm |
| Weight (net) | 2.435kg |
| Type of installation | Mounting rail system installation, Light structure |

Dimensions

| | | |
|---|-----------|--------|
| L | 2302.5 mm | Length |
| B | 63 mm | Width |
| H | 46 mm | Height |

DEEP-LINK

<https://www.regiolux.de/en/article/19282251100>

